



# T2DOC

## Tall Two Drawer Oven Cabinet

**\*\*Standard 3" wide rails above and below cutout, specify if another dimension is required**

**NOTE:** Appliance openings in frames will not have a beaded perimeter when ordered on beaded inset cabinetry. Designer must specify in writing if the appliance opening is to have a bead.

\*\*For figuring reveals for install kits, doors and drawer fronts overlay the oven rail by the following standard amounts:

| Hinge                                       | Overlay   |
|---|-----------|
| FFA   | 1 3/8"    |
| FOL-C                                       | 1 1/4"    |
| SOL-C/SOL-K                                 | 1/2"      |
| SOL-K LIPPED                                | 5/16" *** |
| Specify if another dimension is desired *** |           |

\*\*\*SOL-K Lipped overlays cannot be modified

Provide the following dimensions:

A= \_\_\_\_\_ Overall cabinet width

B= \_\_\_\_\_ Overall cabinet height

C= \_\_\_\_\_ Ht. cutout to start from floor (recommended ht. of 20 1/2" to allow for two std. 4" drawer boxes)

D\*= \_\_\_\_\_ Oven cutout width

E= \_\_\_\_\_ Oven cutout height

\*Cutout may be no wider than 1 1/2" less the overall cabinet width, see chart

| Cabinet width | Max cutout width* |
|---------------|-------------------|
| 24"           | 22 1/2"           |
| 27"           | 25 1/2"           |
| 30"           | 28 1/2"           |
| 33"           | 31 1/2"           |
| 36"           | 34 1/2"           |

